

# D65 BIT SHANK



Specifications	Metric	Imperial
Minimum Hole Size	155mm	6.1"
Shank Length	231mm	9.1"
Number of Splines	12	
Hammer Model	KGR D65	

Diameter		Part Number	No. x Button Dia. (mm)			Flushing holes	Weight Approx.	
mm	inch		Gauge	Face	Concave/convex		Kgs.	Lbs.
<b>Flat Face</b>								
152	6"	54-61BY152S	8x16.6	9x16		2	21.4	47.2
155	6 1/8"	54-61BY155S	8X16.6	9X16		2	22.2	48.9
158	6 1/4"	54-61BY158S	8X16.6	10X16		2	23	50.7
165	6 1/2"	54-61BY165S	10X16.6	10X16		2	23.6	52
165	6 1/2"	54-61BL165S	10X18	10X18		2	24.2	53.4
172	6 3/4"	54-61BY172S	10X16.6	11X16		2	25	55.1
178	7"	54-61BY178S	10x16.6	12x16		2	25.5	56.2
184	7 1/4"	54-61BY184S	10x16.6	13x16		2	26.5	58.4
191	7 1/2"	54-61BY191S	10x16.6	14x16		2	27.4	60.4
203	8"	54-61BY203S	10x16.6	15x16		2	29.2	64.4
216	8 1/2"	54-61BY216S	10x16.6	18x16		2	32.7	72.1
<b>Concave</b>								
155	6 1/2"	54-61CY155S	8x16.6	4x16	6x16	2	22	48.5
165	6 1/2"	54-615Y165S	9x16.6	3x16	6x16	3	23.5	51.8
165	6 1/2"	54-61CY165S	10x16.6	4x16	8x16	2	23.9	52.7
<b>Convex</b>								
155	6 3/4"	54-61HY155S	8x16.6	3x16	6x16	2	22.2	48.9
165	6 1/2"	54-61KY165S	9x16.6	4x16	6x16	3	23.5	51.8
165	6 1/2"	54-61L165S	10x18	4x18	8x18	2	24.2	53.4