



Specifications	Metric	Imperial
Minimum Hole Size	165mm	6.5"
Shank Length	253.5mm	10"
Number of Splines	12	
Hammer Model	KGR QL60	

Diameter		Part Number	No. x Button Dia. (mm)			Flushing holes	Weight Approx.	
mm	inch		Gauge	Face	Concave/convex		Kgs.	Lbs.
Flat Face								
165	6 1/2"	54-60BY165S	10x16.6	10x16		2	25	55.1
165	6 1/2"	54-605Y165S	9x16.6	10x16		3	25	55.1
165	6 1/2"	54-60BN165S	8x18	10x16		2	25.3	55.8
171	6 3/4"	54-605L171S	18x9	18x9		3	27.2	60
178	7"	54-605Y178S	9x16.6	11x16		3	27.5	60.6
190	7 1/2"	54-60BY190S	10x16.6	13x16		2	29.5	65
Concave								
159	6 1/4"	54-60CN159S	8x18	6x16	3x16	2	23.8	52.5
165	6 1/2"	54-60CN165S	10x18	8x16	4x16	2	24.8	54.7
171	6 3/4"	54-60CN171S	10x18	8x16	4x16	2	27.3	60.2
171	6 3/4"	54-606N171S	9x18	6x16	4x16	3	27.3	60.2
190	7 1/2"	54-60CY190S	10x16.6	8x16	6x16	2	28.9	63.7
203	8"	54-60CY203S	10x16.6	8x16	8x16	2	30	66.1
Convex								
165	6 1/2"	54-60KY165S	9x16.6	6x16	2x16	3	25.3	55.8
171	6 3/4"	54-60KL171S	9x18	6x18	2x18	3	27.5	60.6