



Specifications	Metric	Imperial
Minimum Hole Size	200mm	7 7/8"
Shank Length	350mm	13.78"
Number of Splines	10	
Hammer Model	KGR DHD380	

Diameter		Part Number	No. x Button Dia. (mm)			Flushing holes	Weight Approx.	
mm	inch		Gauge	Face	Concave/convex		Kgs.	Lbs.
<b>Flat Face</b>								
152	6"	54-62BY152S	8x16.6	8x16		2	26.8	59.1
165	6 1/2"	54-62BY165S	8x16.6	10x16		2	28.6	63
172	6 3/4"	54-62BY172S	8x16.6	10x16		2	30.3	66.8
178	7"	54-62BY178S	8x16.6	12x16		2	30.6	67.5
<b>Concave</b>								
159	6 1/4"	54-626Y159S	9x16.6	6x16	3x16	3	26	57.3
165	6 1/2"	54-626Y165S	9x16.6	6x16	3x16	3	28	61.7
171	6 3/4"	54-626Y171S	9x16.6	6x16	4x16	3	30	66.1
178	7"	54-626Y178S	9x16.6	6x16	5x16	3	30.5	67.2
190	7 1/2"	54-626Y190S	9x16.6	6x16	6x16	3	31.8	70.1
200	7 7/8"	54-626Y200S	9x16.6	6x16	9x16	3	33	72.7
203	8"	54-626Y203S	9x16.6	6x16	9x16	3	33.3	73.4
216	8 1/2"	54-626Y216S	9x16.6	6x16	10x16	3	35.6	78.5
222	8 3/4"	54-626Y222S	9x16.6	6x16	11x16	3	36.8	81.1
229	9"	54-626Y229S	9x16.6	6x16	12x16	3	37.1	81.8